



product description: the clamps are designed to attach steel pipes to the pad
the clamps are also available for systems maintaining functionality during a fire (see catalogue Systems maintaining functionality during a fire)

material: steel

temperature resistance: -60 - +250 °C

classification according to EN 61386-25:12 for configuration S: 3456210

classification according to EN 61386-25:12 for configuration F: 3456410

mechanical protection according to EN 50102: IK09

fire resistance system: P 90-R, E 90, PS 90

meets the requirements: EN 61386-1 ed.2:09, EN 61386-25:12, EN 50102, ČSN 73 0895, DIN 4102-12, STN 92 0205

storage: EN 60721-3-1



surface: S - Sendzimir galvanized, zinc layer 15 - 27 µm, replaces shop primer, medium corrosion resistance - group 2
F - hot-galvanized, průměrná vrstva zinku 45 µm (min. 35 µm), high corrosion resistance - group 4

| item number | di (mm) | A (mm) | weight 1pc (kg) | package (pc) | for pipes |
|--------------------|------------|-----------|--------------------|-----------------|---|
| 5216E ZNM_S | 15-18 | 6,3x9,8 | 0,02 | 1 / 100 | 6016E..., 6216E... |
| 5220 ZNM_S | 19-23 | 6,3x9,8 | 0,03 | 1 / 100 | 6013..., 6213..., 6016..., 6216..., 6020..., 6220... |
| 5225 ZNM_S | 24-28 | 6,3x9,8 | 0,04 | 1 / 100 | 6021..., 6221..., 6025..., 6225... |
| 5232 ZNM_S | 30-40 | 6,3x9,8 | 0,04 | 1 / 50 | 6029..., 6229..., 6032..., 6232..., 6040..., 6240... |
| 5250 ZNM_S | 39-52 | 6,3x9,8 | 0,07 | 1 / 25 | 6036..., 6236..., 6050..., 6250... |
| 5263 ZNM_S | 53-63 | 6,3x9,8 | 0,08 | 1 / 25 | 6042..., 6242..., 6063..., 6263... |
| 5216E ZN_F | 15-19 | 6,3x9,8 | 0,02 | 1 / 50 | 6016E..., 6216E... |
| 5220 ZN_F | 19-24 | 6,1x9,8 | 0,03 | 1 / 50 | 6013..., 6213..., 6016..., 6216..., 6020..., 6220... |
| 5225 ZN_F | 24-29 | 6,1x9,8 | 0,04 | 1 / 50 | 6021..., 6221..., 6025..., 6225... |
| 5232 ZN_F | 29-38 | 6,1x9,8 | 0,05 | 1 / 25 | 6029..., 6229..., 6032..., 6232... |
| 5240 ZN_F | 38-47 | 6,1x9,8 | 0,06 | 1 / 20 | 6036..., 6236..., 6040..., 6240... |
| 5250 ZN_F | 47-55 | 6,1x9,8 | 0,07 | 1 / 20 | 6042..., 6242..., 6050..., 6250... |
| 5263 ZN_F | 55-63 | 6,3x9,8 | 0,08 | 1 / 20 | 6063..., 6263... |