


**KOPOFLEX®**



product description: flexible double-coated self-snuffing pipe designed for mechanical protection of all kinds of power and data wiring  
 fire spread test according to EN 61386-1  
 the product may be subject to ordinary surface mechanical damage (marks, dents, scratches and rib deformation) of the outer wall of the pipe due to manufacturing technology or transport, which do not affect the functionality of the product

material: HDPE  
 halogen-free: yes  
 self-snuffing: yes  
 installation temperature: -25 - +90 °C  
 operating temperature: -55 - +90 °C  
 fire class for underlying material: A1-F  
 UV stable: no  
 mechanical resistance: 450 N / 20 cm  
 protection types: IP40  
 meets the requirements: EN 61386-1 ed.2:09  
 storage: ČSN 64 0090  
 length tolerance: ± 0,5 m



chemical resistance: YES: acetone, amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
 NO: anilin, chlorinated hydrocarbons, tetrachlorocarbon

item number	dn outer Ø (mm)	di min. inner Ø (mm)	min. bending radius (mm)	length = package (m)	package weight (kg)	weight (kg/package)	color	comment
<b>KF 09110_SKA</b>	110	94	400	50	124x60	25,0	light grey	to order